

Designation	MODEL		XPT30/27x48	
	Type	--	low lift walkie	
Capacity	lbs.	3000		
Power	-	battery		
Load Center	in.	24		
Performance	Maximum Travel Speed - Loaded	mph	2.9	
	Maximum Travel Speed - Unloaded	mph	3.7	
	Maximum Lifting Speed - Loaded	in./sec	2.2	
	Maximum Lowering Speed - Loaded	in./sec	2.2	
	Minimum Turning Radius	in.	56.5	
	Minimum Aisle Width	in.	68	
	Gradeability (Laden / Unladen)	%	5 / 7	
	Control	-	transistor, stepless	
	Brake	-	electromagnetic	
	Voltage / Amp Hour / Charger Voltage	V/AH/V	24 / 60 / 110	
	Motor	Drive	HP	0.8
		Lift	HP	1.07
Chassis	Lowered Fork Height	in.	3.3	
	Raised Fork Height	in.	8	
	Body Height	in.	27.2	
	Overall Body Length	in.	64	
	Overall Body Width	in.	28	
	Handle Width	in.	17	
	Fork Length	in.	48	
	Fork Width O.D.	in.	27	
	Individual Fork Width	in.	6.3	
	Fork Thickness	in.	1.8	
	Battery Compartment Size (L*W*H)	in.	n/a	
	Minimum Ground Clearance	in.	1	
Wheels	Wheel Type Drive / Load	in.	poly / poly	
	Wheel Base	in.	56.89 / 59.2	
	Drive Wheel Dia. x W / Qty	in.	10.5 x 2.5 / x1	
	Load Wheel Dia. x W / Qty	in.	2.9 x 3.9 / x2 single	
	Stabilizer Dia. x W / Qty	in.	3.9 x 1.6 / x2	
Weight	Service weight with standard battery pack	lbs.	610	